

Chrome Steel Precision Spindle Bearings - B types

Selecione Consulta		Tamaño básico (mm)			ra min mm	Masa ≈ (kg)	Capacidad de carga Cr (kN)	Cor Código de (kN) rodamiento
		D	D	B				
10	26	8	0.3	0.02	5.3	2.5	B7000C.T.P4S.UL	
10	26	8	0.3	0.02	5.1	2.4	B7000E.T.P4S.UL	
12	28	8	0.3	0.02	5.85	2.9	B7001C.2RSD.T.P4S.UL	
12	28	8	0.3	0.02	5.85	2.9	B7001C.T.P4S.UL	
12	28	8	0.3	0.02	5.6	2.8	B7001E.2RSD.T.P4S.UL	
12	28	8	0.3	0.02	5.6	2.8	B7001E.T.P4S.UL	
15	32	9	0.3	0.03	6.2	3.4	B7002C.2RSD.T.P4S.UL	
15	32	9	0.3	0.03	6.2	3.4	B7002C.T.P4S.UL	
15	32	9	0.3	0.03	6	3.25	B7002E.T.2RSD.T.P4S.UL	
15	32	9	0.3	0.03	6	3.25	B7002E.T.P4S.UL	
17	35	10	0.3	0.04	8.65	4.9	B7003C.2RSD.T.P4S.UL	
17	35	10	0.3	0.04	8.65	4.9	B7003C.T.P4S.UL	
17	35	10	0.3	0.04	8.3	4.75	B7003E.2RSD.T.P4S.UL	
17	35	10	0.3	0.04	8.3	4.75	B7003E.T.P4S.UL	
20	42	12	0.6	0.7	10.4	6	B7004C.2RSD.T.P4S.UL	
20	42	12	0.6	0.7	10.4	6	B7004C.T.P4S.UL	
20	42	12	0.6	0.07	10	5.7	B7004E.2RSD.T.P4S.UL	
20	42	12	0.6	0.07	10	5.7	B7004E.T.P4S.UL	
25	47	12	0.6	0.08	14.6	9.15	B7005C.2RSD.T.P4S.UL	
25	47	12	0.6	0.08	14.6	9.15	B7005C.T.P4S.UL	
25	47	12	0.6	0.08	13.7	8.65	B7005E.2RSD.T.P4S.UL	
25	47	12	0.6	0.08	13.7	8.65	B7005E.T.P4S.UL	
30	55	13	1	0.12	15	10.2	B7006C.2RSD.T.P4S.UL	
30	55	13	1	0.12	15	10.2	B7006C.T.P4S.UL	
30	55	13	1	0.12	14.3	9.8	B7006E.2RSD.T.P4S.UL	
30	55	13	1	0.12	14.3	9.8	B7006E.T.P4S.UL	

Chrome Steel Precision Spindle Bearings - B types

35	62	14	1	0.16	19	13.7	B7007C.2RSD.T.P4S.UL	
35	62	14	1	0.16	19	13.7	B7007C.T.P4S.UL	
35	62	14	1	0.16	18.3	12.9	B7007E.2RSD.T.P4S.UL	
35	62	14	1	0.16	18.3	12.9	B7007E.T.P4S.UL	