

N300 Series

sélectionner Demande		La désignation	Dimensions principales (mm)						Capacités de charge de base (KN)		Vitesse limitée (tr/min)	Poids (kg)
			ré	ré	B	rs	min	rs	1min	Dynamique(Cr)	Statique (Cor)	
N308	40	90	23	1.5	1.5	58.5	57		8000	9400	0.643	
N309	45	100	25	1.5	1.5	74	71		7200	8400	0.857	
N310	50	110	27	2	2	87	86		6500	7700	1.11	
N311	55	120	29	2	2	111	111		5900	7000	1.42	
N312	60	130	31	2.1	2.1	124	126		5500	6500	1.76	
N313	65	140	33	2.1	2.1	135	139		5100	6000	2.18	
N314	70	150	35	2.1	2.1	158	168		4700	5500	2.65	
N315	75	160	37	2.1	2.1	190	205		4400	5200	3.21	
N316	80	170	39	2.1	2.1	190	207		4100	4800	3.77	
N317	85	180	41	3	3	212	228		3900	4600	4.44	
N318	90	190	43	3	3	240	265		3700	4300	5.18	
N319	95	200	45	3	3	259	285		3400	4000	5.99	
N320	100	215	47	3	3	299	335		3300	3800	7.32	
N321	105	225	49	3	3	320	360		3100	3700	8.33	
N322	110	240	50	3	3	360	400		3000	3500	9.77	
N324	120	260	55	3	3	450	510		2700	3200	12.5	
N326	130	280	58	4	4	560	665		2500	2900	17	
N328	140	300	62	4	4	615	745		2300	2700	20.7	
N330	150	320	65	4	4	665	805		2100	2500	24.7	