

TAC B Series



select Inquiry	Boundary Dimensions (mm)						Reference Dimensions (mm)				Recommended Grease Quantities (cc/Bearing)	Contact Angle(Degree)	Limiting Speeds(min-1)	GreaseOil Mass(kg)
	d	D	B	r (min.)	r1 (min.)	d1	d2	D1	D2					
15	47	15	1	0.6	27.2	34	34	39.6	2.2	60	6900	9200	0.146	
15	47	15	1	0.6	25.1	30.8	36	41.8		60	6900		0.146	
17	47	15	1	0.6	27.2	34	34	39.6	2.2	60	6900	9200	0.14	
17	47	15	1	0.6	25.1	30.8	36	41.8		60	6900		0.14	
20	47	15	1	0.6	27.2	34	34	39.6	2.2	60	6900	9200	0.135	
20	47	15	1	0.6	25.1	30.8	36	41.8		60	6900		0.135	
25	62	15	1	0.6	37	45	45	50.7	3	60	5200	6900	0.252	
25	62	15	1	0.6	34.3	40.5	46.5	52.9		60	5200		0.252	
30	62	15	1	0.6	39.5	47	47	53.2	3.2	60	4900	6400	0.224	
30	62	15	1	0.6	36.8	43	49	55.4		60	4900		0.224	
35	72	15	1	0.6	47	55	55	60.7	3.8	60	4100	5800	0.31	
35	72	15	1	0.6	44.3	50.5	56.5	62.9		60	4100		0.31	
40	72	15	1	0.6	49	57	57	62.7	3.9	60	4100	5500	0.275	
40	72	15	1	0.6	46.3	52.5	58.5	64.9		60	4100		0.275	
40	90	20	1	0.6	57	68	68	77.2	8.8	60	3500	4600	0.674	
40	90	20	1	0.6	54	64	70	79.4		60	3500		0.674	
45	75	15	1	0.6	54	62	62	67.7	4.2	60	3700	4900	0.27	
45	100	20	1	0.6	64	75	75	84.2	9.7	60	3000	4100	0.842	
45	100	20	1	0.6	61	71	77	86.4		60	3000		0.842	
50	100	20	1	0.6	67.5	79	79	87.7	10.2	60	3000	3900	0.778	
50	100	20	1	0.6	64.5	74.5	80.9	90.3		60	3000		0.778	
55	100	20	1	0.6	67.5	79	79	87.7	10.2	60	3000	3900	0.714	
55	100	20	1	0.6	64.5	74.5	80.9	90.3		60	3000		0.714	
55	120	20	1	0.6	82	93	93	102	12	60	2500	3500	1.23	
60	120	20	1	0.6	82	93	93	102	12	60	2500	3500	1.16	