

6900 Series

sélectionner	Demande	Désignation du roulement	Dimension (mm)				Capacités de charge de base (kN)		Cotes de vitesse (tr/min)		Poids (Kg)
			ré	ré	B	rs min	Cr	Cor	Graisse	Huile	
6900	10	22	6	0.3	2.7	1.27	30000	36000	0.009		
6901	12	24	6	0.3	2.89	1.46	27000	32000	0.011		
6902	15	28	7	0.3	3.65	2	24000	28000	0.016		
6903	17	30	7	0.3	4.65	2.58	22000	26000	0.018		
6904	20	37	9	0.3	6.4	3.7	19000	23000	0.036		
6905	25	42	9	0.3	7.05	4.55	16000	19000	0.042		
6906	30	47	9	0.3	7.25	5	14000	17000	0.048		
6907	35	55	10	0.6	9.55	6.85	12000	15000	0.074		
6908	40	62	12	0.6	12.2	8.9	11000	13000	0.11		
6909	45	68	12	0.6	13.1	10.4	9000	12000	0.128		
6910	50	72	12	0.6	13.4	11.2	8900	11000	0.132		
6911	55	80	13	1	16	13.3	8200	9600	0.18		
6912	60	85	13	1	16.4	14.3	7600	8900	0.193		
6913	65	90	13	1	17.4	16.1	7000	8200	0.206		
6914	70	100	16	1	23.7	21.2	6500	7700	0.334		
6915	75	105	16	1	24.4	22.6	6100	7200	0.353		
6916	80	110	16	1	24.9	24	5700	6700	0.373		
6917	85	120	18	1.1	32	29.6	5400	6300	0.536		
6918	90	125	18	1.1	33	31.5	5100	6000	0.554		
6919	95	130	18	1.1	33.5	33.5	4800	5700	0.579		
6920	100	140	20	1.1	41	39.5	4500	5300	0.785		
6921	105	145	20	1.1	42.5	42	4300	5100	0.816		
6922	110	150	20	1.1	43.5	44.5	4100	4800	0.849		
6924	120	165	22	1.1	53	54	3800	4400	1.15		
6926	130	180	24	1.5	65	67.5	3500	4100	1.52		

6900 Series

6928	140	190	24	1.5	66.5	71.5	3200	3800	1.62
6930	150	210	28	2	85	90.5	3000	3500	2.47
6932	160	220	28	2	87	96	2800	3300	2.61
6934	170	230	28	2	86	95.5	2600	3100	2.74
6936	180	250	33	2	110	119	2400	2900	4.76