

Cylindrical Roller Bearings, Single Row, Super-precision

sélectionner Demande		Dimensions de la limite (mm)				Capacités de charge de base (kN)		Diamètre cercle circonscrit du galet (mm) (référence)		Masse (kg) (environ)	Vitesses limites (min-1)	GraisseHuile
		ré	ré	B	r (min.)	r1 (min.)	Cr (Dynamique)	C0r (statique)				
30	55	13	1	0.6	19.7	19.6	48.5	0.135	19000	31000		
35	62	14	1	0.6	22.6	23.2	55	0.172	17000	27000		
40	68	15	1	0.6	27.3	29	61	0.213	15000	25000		
45	75	16	1	0.6	32.5	35.5	67.5	0.279	14000	22000		
50	80	16	1	0.6	32	36	72.5	0.286	13000	20000		
55	90	18	1.1	1	37.5	44	81	0.425	12000	18000		
60	95	18	1.1	1	40	48.5	86.1	0.454	11000	17000		
65	100	18	1.1	1	41	51	91	0.483	10000	16000		
70	110	20	1.1	1	50	63	100	0.668	9000	15000		
75	115	20	1.1	1	60	74.5	105	0.7	8500	13700		
80	125	22	1.1	1	63.5	82	113	0.957	7900	12700		
85	130	22	1.1	1	65	86	118	1.067	7500	12100		
90	140	24	1.5	1.1	88	114	127	1.27	7000	11400		
95	145	24	1.5	1.1	83	114	132	1.37	6700	10900		
100	150	24	1.5	1.1	93	126	137	1.46	6400	10400		
105	160	26	2	1.1	112	155	146	1.79	6100	9900		
110	170	28	2	1.1	126	173	155	2.22	5800	9300		
120	180	28	2	1.1	139	191	165	2.34	5400	8700		
130	200	33	2	1.1	172	238	182	3.55	4900	7900		
140	210	33	2	1.1	164	240	192	3.78	4600	7500		
150	225	35	2.1	1.5	202	294	206	4.56	4300	4800		
160	240	38	2.1	1.5	238	340	219	5.59	4000	4500		
170	260	42	2.1	2.1	287	415	237	7.85	3600	4000		
180	280	46	2.1	2.1	355	510	255	9.76	3400	3800		
190	290	46	2.1	2.1	365	535	265	10.4	3200	3600		
200	310	51	2.1	2.1	390	580	281	13.5	3000	3400		
220	340	56	3	3	500	750	310	17.4	2600	3000		
240	360	56	3	3	530	820	330	18.6	2400	2800		
260	400	65	4	4	645	1000	364	27.6	2200	2600		
300	460	74	4	4	885	1400	420	42.2	1800	2000		