

High Temperature Y-bearing Square Flanged Units

sélectionner Demande		taille (mm)										Capacité de charge de base (kN)		Modèle	
		ré	A1	A2	B	J	L	N	g	T	Co	poids (kg)	With stamped steel cage Y-bearing unit	With graphite crown cage Y-bearing unit	
3/4	29,5	11	31	63,5	86	11,1	10	37,3	6,55	0,60	FY3/4TF/VA201	FY3/4TF/VA228			
1	30	12	34,1	70	95	12,7	10	38,8	7,8	0,77	FY1.TF/VA201	FY1.TF/VA228			
1 3/16	32,5	13	38,1	82,5	108	12,7	10	42,2	11,2	1,10	FY1.3/16TF/VA201	FY1.3/16TF/VA228			
1 1/4	34,5	13	42,9	92	118	14,3	12	46,4	15,3	1,40	FY1.1/4TF/VA201	FY1.1/4TF/VA228			
1 7/16	34,5	13	42,9	92	118	14,3	12	46,4	15,3	1,40	FY1.7/16TF/VA201	FY1.7/16TF/VA228			
1 1/2	38,5	14	49,2	101,5	130	14,3	12	54,2	19	1,90	FY1.1/2TF/VA201	FY1.1/2TF/VA228			
1 11/16	39	14	49,2	105	137	15,9	14	54,2	21,6	2,10	FY1.11/16TF/VA201	FY1.11/16TF/VA228			
1 3/4	39	14	49,2	105	137	15,9	14	54,2	21,6	2,10	FY1.3/4TF/VA201	FY1.3/4TF/VA228			
1 15/16	43	15	51,6	111	143	15,9	14	60,6	23,2	2,50	FY1.15/16TF/VA201	FY1.15/16TF/VA228			
2	47,5	16	55,6	130	162	19	16	64,4	29	3,75	FY2.TF/VA201	FY2.TF/VA228			
2 3/16	47,5	16	55,6	130	162	19	16	64,4	29	3,55	FY2.3/16TF/VA201	FY2.3/16TF/VA228			
2 7/16	52	17	65,1	143	175	19	16	73,7	36	4,50	FY2.7/16TF/VA201	FY2.7/16TF/VA228			